


U.S. Patent Application for

**MULTIPLE VIEWING ANGLE COVER
HAVING INTEGRAL LIGHT PIPE**

By:

**Mark S. Schladenhauffen
Hassan R. Manjunath
Patrick J. Delaney, III**

EXPRESS MAIL MAILING LABEL	
NUMBER	EL 652 335 920 US
DATE OF DEPOSIT	June 14, 2001
<small>Pursuant to 37 C.F.R. § 1.10, I hereby certify that I am personally depositing this paper or fee with the U.S. Postal Service, "Express Mail Post Office to Addressee" service on the date indicated above in a sealed envelope (a) having the above-numbered Express Mail label and sufficient postage affixed, and (b) addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.</small>	
074/01 Date	 Lynda Howell

MULTIPLE VIEWING ANGLE COVER HAVING INTEGRAL LIGHT PIPE

BACKGROUND OF THE INVENTION

1. Field Of The Invention

The present invention relates generally to the field of enclosures for electronic devices. More particularly, the invention relates to a technique for optically coupling the light produced by a light emitting source housed within an enclosure to the exterior of the enclosure via a light pipe integrated into a cover of the enclosure, the cover enabling a viewer to view the light from multiple viewing angles around the enclosure.

2. Description Of The Related Art

Many electronic devices are designed to produce a visual output. The visual output may provide a myriad of information in a myriad of ways. For example, a device may provide text and images on a computer monitor. Alternatively, a device's visual output may be a light to indicate that the device is operating.

The type of visual output used may be dictated by a number of factors, such as the information to be conveyed and the operating environment of the device. For example, a production line may utilize one or more electronic sensors to provide an operator with information regarding the status of production. An electronic sensor may be placed anywhere along the production line. The electronic sensor may be located at floor level, below floor level, or above floor level, depending on the orientation of the production line. Typically, the visual output of a sensor is visible from only one location from the workflowloor.

Many electronic devices utilize a light emitting diode (LED) to convey information. In some instances, an LED may be mounted on an exterior surface of an electronic device. However, the LED is more susceptible to damage when mounted on the exterior of an electronic device. Additionally, electrical wiring typically must be routed to the LED to enable it to operate. In some instances, an LED, or LED's, may act

as nuisance sources of electro-optical/electro-magnetic noise. LED's also have been mounted on circuit boards housed within a protective enclosure. The light from an LED may be coupled through a window to the outside. Alternatively, a light guide, such as a fiber optic cable, may be used to direct light from the LED to the outside of the enclosure.

5 The assembly of the device is complicated by the need to route the light guide from the LED to a cover of the enclosure. Additionally, in both of these configurations the viewing angle for viewing the light from the LED is limited. In the former, a viewer is only able to see the light from the LED when the viewer is positioned directly in the line of sight of the window and the LED. In the latter, the process of reflecting the light

10 internally through the optical fiber results in the optical fiber effectively producing a unidirectional beam of light. As a result, a viewer located directly across from the fiber optic cable may be able to see the light from the LED but a viewer located on another side of the device may not. In a production environment, where an operator may be constantly changing positions, an electronic device having a visual output with a limited

15 viewing angle may be problematic to production. For example, a production line may have a sensor to detect various operating conditions on the line. The sensor may utilize one or more LED's to indicate these operating conditions to an operator. If the operator cannot see the output of the LED's from the operator's location, either the information will be lost or the operator will have to move to a another location where the output of the

20 LED can be seen.

There is a need, therefore, for an improved technique for optically coupling the light from an LED housed within an enclosure to a viewer located on the outside of the enclosure in a manner that will enable the light to be seen from multiple viewing angles

25 around the electronic device.

SUMMARY OF THE INVENTION

The present invention provides a technique for providing visual information from an electronic device designed to respond to these needs. According to

30 one aspect of the technique, an electronic device housing a light source is featured. The

electronic device has a protective enclosure formed from a protective housing and a cover secured to the protective housing. The cover forms a light guide for guiding a first portion of light from the light source to a first surface portion of the cover. A second surface portion of the cover is adapted to totally internally reflect the first portion of the light to the first surface portion. The electronic device may receive power via a cable inserted into the protective housing. The cover may have a guide portion adapted to guide the cable to a desired position within the housing and to secure the cable between the protective housing and the cover as the cover is secured to the protective housing.

According to another aspect of the present invention, a protective cover for an enclosure is featured. The protective cover has a first surface region and a second surface region. The first surface region is oriented on a first side of the enclosure and the second surface region is oriented on a second side of the enclosure. A first portion of the cover is adapted to receive light from a light source and to totally internally reflect the light to the first surface region and the second surface region. The cover may have a guide portion adapted to guide a power cable to a desired position within the housing and to secure the cable between the protective housing and the cover as the cover is secured to the protective housing.

According to another aspect of the present invention, a method of providing visual information from an electronic device is featured. The method produces light from a light source housed within a protective enclosure of the electronic device. The light from the light source provides data from the electronic device. The method also adapts the electronic device to guide the light from the light source to a plurality of surface portions of the enclosure. Total internal reflection is used to guide the light through a portion of the cover of the enclosure. The method also refracts the light at the plurality of surface portions so that the light is visible from a plurality of sides of the enclosure.

According to another aspect of the present invention, a method of manufacturing a cover for an electronic device is featured. The method identifies a moldable material's

critical angle for total internal reflection of light from a light source. The light source is housed within the electronic device. The method also designs a shape for the cover that uses total internal reflection to direct light from the light source to a surface portion of the cover. The method also provides for molding the cover to the designed shape.

5

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and other advantages of the invention will become apparent upon reading the following detailed description and upon reference to the drawings in which:

10

Figure 1 is a first perspective view of an electronic sensor having an enclosure with a cover having integral light pipes to optically couple light from a plurality of LED's housed within the enclosure to a surface portion of the cover, according to an exemplary embodiment of the present invention;

15

Figure 2 is a second perspective view of the electronic sensor of Figure 1;

Figure 3 is an exploded view of the components of the electronic sensor of Figure 1;

20

Figure 4 is a rear elevational view of a cover having integral light guides, according to an exemplary embodiment of the present invention;

25

Figure 5 is a rear perspective view of the cover of Figure 4;

Figure 6 is a cross-sectional view of the light guide portion of the cover, taken generally along line 6-6 of Figure 4;

30

Figure 7 is a detailed view of a portion of the housing; and

Figure 8 is an elevational view of the interior of a protective housing, according to an exemplary embodiment of the present invention.

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

Turning now to the drawings, and referring first to Figures 1 and 2, an electronic device, designated generally by the reference number 20, is illustrated. In the illustrated embodiment, the electronic device 20 is an optical sensor. However, the present invention is not limited to sensors. The electronic device has a protective enclosure 22 that utilizes a housing 24 and a cover 26 to house and protect components of the electronic device 20. In the illustrated embodiment, the cover 26 is securable to the housing 24. The protective enclosure 22 has a generally cubic shape. However, in this embodiment, the housing 24 is configured with a hollow extension 28 that extends outward from a flat surface 30 of the housing 24. In this embodiment, the hollow extension 28 enables an optical emitter and an optical receiver located within the housing 24 to have an unobstructed view of a target.

In the illustrated embodiment, a circuit board (not shown) having a plurality of light emitting diodes (LED's) (not shown) is housed within the housing 24 and cover 26. Alternatively, another device for emitting light may be used, such as a light bulb or semiconductor laser. Each LED may provide light of a single color or a plurality of colors. Furthermore, each of the plurality of LED's may provide one or more different colors of light. Additionally, the light from the LED's may be pulsed or continuous.

The cover 26 is adapted to form integral light guides for coupling the light from the LED's. The light guides use internal reflection to guide the light from the LED to the exterior of the enclosure 22. The cover 26 is configured with a generally flat portion 32 that extends generally over one side of the enclosure 22. In the illustrated embodiment, the cover 26 is comprised of a molded polymeric material, such as Trogamid®. Trogamid® is a transparent nylon material that has an average transmittance of 90% over the visible range of light, i.e., 350-680 nm. Generally, the surface of the cover 26 is formed with a relatively rough surface texture that makes the cover relatively opaque. However, in the illustrated

embodiment, the cover 26 has a plurality of smooth strips 34 that are formed slightly recessed from the generally flat portion of the cover 26 during the molding process. The smooth strips 34 are made smooth by polishing the appropriate portion of the mold that forms the smooth strip. Each smooth strip 34 forms a portion of a light guide for an LED.

5 The smooth surface of each smooth strip 34 enables light to be internally reflected at the surface of each smooth strip 34 in a precise manner. Additionally, the smooth surface of each strip 34 enables a portion of the light to be refracted through the surface without scattering. Thus, the smooth strips 34 in the illustrated embodiment serve two purposes: internally reflecting a portion of the light from an LED and refracting a portion of the light

10 from the LED.

In the illustrated embodiment, the cover 26 also is configured with a plurality of inverted pyramid portions 36 that are located on a second side of the enclosure 22. In this embodiment, light from an LED is internally reflected through the cover 26 to an inverted pyramid portion 36. In the exemplary embodiment, the inverted pyramid portions 36 also are formed with a smooth surface during the molding process. The shape of an inverted pyramid portion 36 causes light that has been internally reflected through the cover to be refracted in many directions. This enables the light from an LED to be seen from multiple sides of the enclosure 22, such as the front, back, left and right. The inverted pyramid

15 portions 36 may have different heights or may be otherwise be configured differently to assist in identification. For example, the far left pyramid 36 of Fig. 1 is taller than the other two pyramids 36. This enables a viewer to have an unobstructed view of light from the far left pyramid 36. Additionally, the portion 38 of the light that is coupled to the strips 34 is transmitted through the strips 34 and is visible from one or more sides of the enclosure. In

20 fact, the cover 26 could be configured to transmit light in a myriad of configurations. For example, each LED could be coupled to a second inverted pyramid portion in addition to, or instead of, a smooth strip 34, or vice versa. In this configuration, an inverted pyramid portion 36 may be disposed on opposite sides of the enclosure 22. The cover 26 may be configured to transmit light from additional or different sides of the enclosure 22.

25

30

Referring generally to Figure 3, the electronic device 20 is assembled from a plurality of components. A printed circuit (PC) board 42 is used to couple the various electronic components of the device 20. A transmitter 44 and a sensor 46 are located on one side of the PC board 42. Several LED's 48 are located on the other side of the PC board 42. A window 50 and a lens 52 are secured to the hollow extension 28 portion of the housing 24. The window 50 prevents contaminants from entering the interior of the enclosure 22 but is transparent to enable light to enter and exit the enclosure 22. The lens 52 focuses the light onto the optical sensors 46. An optical shield 54 is used to prevent the sensors 46 from being contaminated with light from sources other than light from the target area. In addition, the device 20 has an electronic shield 56 to prevent interference from outside sources of electrical noise. Power is supplied to the electronic components by a conductive cable 58. The conductive cable 58 is secured within the device 20 by a clasp 60. The clasp 60 secures the cable 58 between the cover 26 and the housing 24 when the cover 26 is secured to the housing 24. Also visible in this view are three generally triangular shaped portions 62 of the cover 26. Each triangular shaped portion 62 of the cover 26 is used to receive light from an LED 48 and internally reflect the light to the strip portions 34 and to the inverted pyramid portions 36.

Referring generally to Figures 4 and 5, the cover 26 of the illustrated embodiment is adapted to use total internal reflection to couple light from three LED's 48. However, the cover 26 may be configured to couple light from a greater or lesser number of LED's. The LED's may be used to convey different pieces of information. For example, one of the LED's may indicate that the device has power. Another LED may provide an indication whenever the sensor detects a target object. Another LED may be used to indicate the sensitivity of the detector. Different colors may be used for each LED. In the illustrated embodiment, the cover 26 has three generally triangular shaped portions 62 extending from an interior surface 64 of the cover 26, one for each LED. However, additional triangular shaped portions 62 may be associated with each LED 48. For example, a second triangular shaped portion 62 may be used to couple light from an LED 48 to a second inverted pyramid portion 36.

The cover 26 has a lip 64 that extends from the interior surface 64 around the perimeter of the cover 26. The lip 64 is configured for engagement with a corresponding groove in the housing 24. In this embodiment, the cover 26 also has two openings 68 that align with two corresponding openings in the housing 24. Two securing members, such as threaded fasteners, are inserted through the openings 68 to secure the enclosure 22 to a surface. The cover 26 may have an adjustment hole to enable a screwdriver, or some other tool, to be inserted through the cover to adjust a potentiometer, or some other adjustable component, within the device 20. In the illustrated embodiment, the inverted pyramid portions 36 are located on a surface portion 70 of the cover 26. The surface portion 70 is disposed within a recess in the housing 24 when the cover 26 is secured to the housing 24.

Referring generally to Figure 6, generally, whenever a ray of light is incident on the boundary separating two different optical media, part of the ray is reflected back into the first media and the remainder is refracted as it enters the second media. Refraction is the bending of light as it passes through the boundary between two media. The directions taken by these rays can be described by two well-established laws of nature. The first law states that the angle at which the incident ray strikes the interface of two optical media, the angle of incidence, is exactly equal to the angle the reflected ray makes with the interface, the angle of reflection. The angles of incidence and reflection are commonly measured from a line perpendicular to the interface, known as the normal. Furthermore, the incident ray and the reflected ray lie in the same plane, the reflected ray lying on the opposite side of the normal from the incident ray. The second law states that the sine of the angle of incidence and the sine of the angle of refraction have a constant ratio for all angles of incidence. This constant ratio also is equal to the ratio of the indices of refraction of the two media. The index of refraction, or refractive index, of any optical medium is defined as the ratio between the speed of light in a vacuum and the speed of light in the medium. The refracted ray and the incident ray also lie in the same plane, the refracted ray lying on the opposite side of the normal from the incident ray. This relationship, known as Snell's law, can be written as follows:

$$n_1 \sin \theta_1 = n_2 \sin \theta_2$$

where: n_1 is the index of refraction of the first medium;

θ_1 is the angle of incidence;

5 n_2 is the index of refraction of the second medium; and

θ_2 is the angle of refraction.

However, there is an angle of incidence beyond which no light is refracted through the boundary between the two media. This is known as the critical angle, θ_c . The critical angle is defined as the smallest angle of incidence, in the medium of greater index, for
10 which light is totally reflected, i.e., no light is refracted through the boundary. The equation for finding the critical angle may be derived from Snell's law and can be written as follows:

$$\theta_c = \sin^{-1} (n_2 / n_1)$$

15 where: n_1 is the index of refraction of the first medium;

n_2 is the index of refraction of the second medium; and

θ_c is the critical angle.

In the illustrated embodiment, divergent light rays from an LED 48 are incident on a
20 first surface 72 of a triangular portion 62 of the cover 26. In the illustrated embodiment, the first surface 72 is adapted to collect light from the LED that might be reflected from a flat surface. In the illustrated embodiment, the cover 26 has several surfaces that are adapted to totally internally reflect light from each LED and direct the light to a strip portion 34 and an inverted pyramid portion 36. In this embodiment, the two media at each of the surfaces are
25 air 74 and the material of the cover 26. The portions of the mold used to form the various surfaces are polished so that the surfaces of the cover 26 have a smooth polished texture. This prevents the light incident on the surfaces from being scattered. In the illustrated embodiment, a first ray 76 from the LED 48 is incident on a second surface 78 of the triangular portion 62 of the cover 26. A second ray 80 from the LED 48 is incident on a
30 third surface 82 of the triangular portion 62 of the cover 26. A third ray 84 also is incident

on the third surface 82. In the illustrated embodiment, the third surface 82 is angled approximately 25 degrees in relation to the flat portion 64 of the cover 26.

A line 86 represents the normal to each surface. The index of refraction of air 74 is, approximately, 1. In the illustrated embodiment, the index of refraction of the cover is approximately 1.566 at a wavelength of 589.3 nm. The critical angle, θ_c , for a boundary between the air 74 and the cover 26 is approximately 39.7 degrees, as represented by angle 88. The first, second, and third rays are incident to the second and third surfaces, respectively, at angles greater than the critical angle. Consequently, the first, second, and third rays are totally internally reflected inside the cover 26 towards a fourth surface, the strip portion 34. The first, second, and third rays also are incident to the strip portion 34, at angles greater than the critical angle and are again totally internally reflected. The first ray 76 is incident to a fifth surface 90 and is again totally internally reflected. The first ray 76 is then incident to a first face 92 of the inverted pyramid portion 36. The first ray 76 is incident to the first face 92 at an angle greater than the critical angle and is refracted through the first face 92. The second ray 80 is incident to a sixth surface 94 and, again, is totally internally reflected. The second ray 80 is then incident to the first face 92 of the inverted pyramid portion 36 at an angle less than the critical angle and is refracted through the first face 92. The third ray 84 is incident to a second face 96 of the inverted pyramid portion 36 at an angle less than the critical angle and is refracted through the second face 96. In the illustrated embodiment, the faces of the inverted pyramid are angled at an angle of approximately 45 degrees.

A fourth ray 98 and a fifth ray 100 from the LED 48 are incident on the strip portion 34 of the cover 26. The fourth ray 98 is incident to the strip portion 34 at an angle less than the critical angle and is refracted through the strip portion 34. Thus, a portion of the light from the LED 48 also is guided to and transmitted from the strip portion 34, as well as the inverted pyramid portion 36 of the cover 26. The fifth ray 100 is incident to the strip portion 34 at an angle greater than the critical angle and is totally internally reflected towards the second face 96 of the inverted pyramid portion 36. The fifth ray 100 is incident

to the second face 96 of the inverted pyramid portion 36 at an angle less than the critical angle and is refracted through the second face 96. Please note that the actual number of light rays emanating from the LED 48 is virtually infinite. Additionally, the number of different paths the light rays may make through the cover 26 to the strip portion 34 and the inverted pyramid portions also is virtually infinite.

Referring generally to Figures 7 and 8, the housing 24 has a groove 102 configured to receive the lip 66 of the cover 26. The housing also has a hole 104 for receiving a conductor cable 58. The housing also has a receiving portion 106 for receiving the cable 58. The receiving portion 106 is notched to guide the cable 58 into the enclosure 22 for coupling to the PC board 42. The housing 24 also has a securing portion 108 configured to receive the clasp 60 of the cover 26 when the cover 26 is placed on the housing 24. The securing portion 108 has a serrated surface 110 configured to contact a serrated portion 112 of the clasp 60. The clasp 60 secures the cable 58 between the cover 26 and the housing 24 as the cover 26 is secured to the housing 24. Additionally, the clasp 60 directs the cable 58 to the desired position within the enclosure. No additional pieces are needed to secure the cable within the enclosure.

The housing 24 also has two openings 114 that align with the opening 68 in the cover 26 for securing the enclosure 22 to an external surface. A guide pin 116 is used to align with a guide hole (not shown) in the PC board 42 to properly position the PC board 42. A plurality of guide members 118 are used with the guide pin 116 to properly align the PC board. In addition, the housing 24 has a first orifice 120 and a second orifice 122 therefore. The first orifice 120 enables light, such as infrared light, to be transmitted from a light source within the enclosure 22 to a target. The second orifice 122 enables light from a target to be detected by a sensor 46 within the enclosure.

Referring to Figs. 5 and 7, in the illustrated embodiment, a plurality of securing clips 124 on the housing 24 are used to secure the cover 26 to the housing 24. The securing clips 124 are disposed into openings 126 in corresponding securing member 128 on the

cover 26. The clips 124 are flexible to allow elastic deformation of the clips 124 during insertion of the clips 124 into the openings 126.

5 While the invention may be susceptible to various modifications and alternative forms, specific embodiments have been shown in the drawings and have been described in detail herein by way of example only. However, it should be understood that the invention is not intended to be limited to the particular forms disclosed. For example, the present technique may be used with many different types of electronic devices, including many different types of sensors, such as magnetic sensors, proximity sensors, etc. The
10 invention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the following appended claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
22